



# SWE18UF



◆ **Yanmar engine**

With low noise, low vibration, and easy maintenance of the main components, Yanmar engine is very popular with compact equipment.

◆ **Rich configuration**

Full hydraulic control, automatic shift when walking, retractable chassis, deflectable working device.

◆ **Easy maintenance**

Air filter element, engine oil filter element, oil-water separator, fuel filter element, auxiliary water tank, etc. are accessible. Centralized lubrication from outside makes daily maintenance easy and simple.

◆ **Quick change device**

All kinds of buckets and accessories can be removed or installed quickly.

◆ **Working device pipeline**

Accessory pipelines and hydraulic quick change pipelines are equipped as standard.

ENGINE		UNIT	SWE18UF
Working weight		kg	1880
Capacity of bucket		m <sup>3</sup>	0.04
Engine	Brand		YANMAR
	Type		3TNV80-SSU
	Rated output power	kW/rpm	13.4/2200
Dimension parameters	Transportation length	mm	3582
	Transportation height	mm	2350
	Total width	mm	990/1360
	Counterweight ground clearance	mm	462
	Min. ground clearance	mm	160
	Tail slewing radius	mm	680
	Ground contact length of track	mm	1210
	Track length	mm	1538
	Track gauge	mm	760/1130
	Track width	mm	990/1360
	Creeper tread width	mm	230
	Cab height	mm	2350
	Turntable width	mm	980
	Scope of work	Maximum excavation height	mm
Maximum dumping height		mm	2430
Maximum digging depth		mm	2210
Maximum vertical digging depth		mm	1550
Maximum digging radius		mm	3940
Maximum digging radius on ground		mm	3850
Min. slewing radius		mm	1710
Swing arm length	mm	1800	
Bucket arm length	mm	950/1150	
Bucket arm digging force	kN	12	
Bucket digging force	kN	21	
Speed (high/low)	km/h	3.5/2.0	
Slewing speed	rpm	10	
Fuel tank capacity	L	24.6	
Hydraulic fuel tank capacity	L	18.6	

