



SWE25F



◆ Yanmar engine

With low noise, low vibration, and easy maintenance of the main components, Yanmar engine is very popular with compact equipment.

◆ Excellent performance

Equipped with high-performance hydraulic system and components, the compound actions of swing arm, bucket arm, bucket and rotation are coordinated and smooth, which has left a deep impression in this tonnage level.

◆ Simple and convenient switch control

Monitoring instruments are easy to read and operate.

◆ Easy maintenance

The fully openable door and hood make daily inspection and filter maintenance and replacement simple and convenient. The access door is located at left lower corner, which is very convenient for the maintenance and repair of the multiple unit valve, so as to avoid the trouble of removing the cover.

ENGINE		UNIT	SWE25F
Working weight		kg	2640
Capacity of bucket		m ³	0.08
Engine	Brand		YANMAR
	Type		3TNV80-PSU
	Rated output power	kW/rpm	14.6/2400
Dimension parameters	Transportation length	mm	4262
	Transportation height	mm	2400
	Total width	mm	1500
	Counterweight ground clearance	mm	546
	Min. ground clearance	mm	280
	Tail slewing radius	mm	1050
	Ground contact length of track	mm	1560
	Track length	mm	1990
	Track gauge	mm	1200
	Track width	mm	1500
	Creeper tread width	mm	300
	Cab height	mm	2400
	Turntable width	mm	1380
	Scope of work	Maximum excavation height	mm
Maximum dumping height		mm	3110
Maximum digging depth		mm	2705
Maximum vertical digging depth		mm	1533
Maximum digging radius		mm	4845
Maximum digging radius on ground		mm	4715
Min. slewing radius		mm	2143
Swing arm length	mm	2050	
Bucket arm length	mm	1350	
Bucket arm digging force	kN	14	
Bucket digging force	kN	24	
Speed (high/low)	km/h	4.4/2.6	
Slewing speed	rpm	9	
Fuel tank capacity	L	42.5	
Hydraulic fuel tank capacity	L	30	

